



Spraying Systems Co.®
Experts in Spray Technology

A Guide to Safe and Effective Sanitation

Innovative Spray Products for
Food and Pharmaceutical Processing



Spray
Nozzles



Spray
Control



Spray
Analysis




Spray
Fabrication

Spray Sanitation Applications



**Automated
Tank Washing**

**Equipment and
Conveyor Cleaning**





**Manual
Cleaning**



**Conveyor Cleaning
and Blow Off**



Table of Contents

**Manifolds for Mounting
Spray Nozzles** in CIP conveyor
cleaning applications4

Spray Nozzles for CIP
and clean-up crew use5

Tank Wash Nozzles for CIP
cleaning of process and storage
vessels, and enclosed equipment

Rotating Teflon® Nozzles6

**Controlled-Rotation
Stainless Steel Nozzles**7

Spray Balls8

**Large Vessel
Tank Wash Machines**9

**Reaction-Driven
Rotating Nozzles**10

Stationary Cluster Nozzles ..11

**Lances for Mounting
Tank Wash Nozzles**
in process and storage vessels,
and enclosed equipment12

Spray Guns for the
clean-up crew13

Air Knives for conveyor drying ..14


Air Control Nozzles
for conveyor drying
and spot drying15

Headers and Manifolds

for precision washing of conveyors,
equipment and product


Spraying Systems Co. manufactures fixed or oscillating spray headers and manifolds for a wide variety of applications. For applications that are out of the ordinary, we offer custom fabrication to meet your exacting needs.

Designed specifically for your application, these manifolds improve efficiency in every stage of washing. For exact washing needs custom design features are available.



Custom Sanitation Manifold Spec Illustration

With maximum operating pressure of 150 psi (10.34 bar)




Manifold Options:

- pipe length
- inlet and outlet connectors
- nozzle type
- nozzle connections (drill/tap or welded)
- nozzle spacing and placement
- shower height
- spray angles
- material
- flow rate
- operating pressure
- finish (Ra, grit, electro polish)

Custom High Pressure Sanitation Manifold Spec Illustration

With maximum operating pressure of 800 psi (55.15 bar)



Nozzles

for superior wash performance
in fixed manifolds or handheld spraying

48099 Adjustable WashJet® Nozzle

- Twisting cap varies spray
- Spray angles: 0° - 80°
- Variable spray patterns from a solid stream to a flat fan
- 1/8" and 1/4" NPT or BSPT (F)
- Maximum pressure: 3000 psi (200 bar)
- Material: brass or stainless steel
- Capacity range: .55 to 19.1 gpm (2.0 to 66 l/min)



Solid Stream



Flat (even)

WashJet® Nozzles

- High impact at high pressure
- Spray angles: 0° - 80°
- Solid stream or flat even spray pattern
- 1/8" and 1/4" NPT or BSPT (M)
- Pressure range: 300 psi to 4000 psi (20 to 275 bar)
- Material: stainless steel
- Capacity range: .28 to 13.0 gpm (1.0 to 48 l/min)



Solid Stream



Flat (even)

VeeJet® Nozzles

- Medium impact with even coverage
- Spray angles: 0° - 110°
- 1/8", 1/4", 3/8" and 1/2" NPT or BSPT (M or F)
- Solid stream or flat spray pattern
- Tapered flat fan spray pattern for even overlap coverage
- Pressure range: 5 psi to 500 psi (.3 bar to 35 bar)
- Material: brass or stainless steel
- Nozzle strainer available
- Capacity range: .012 to 88 gpm (.05 to 335 l/min)



Solid Stream



Flat Spray (tapered)

FlatJet® Nozzles

- High impact at low pressure
- Spray angles: 15° - 50°
- 1/8", 1/4", 3/8", 1/2" and 3/4" NPT or BSPT (M or F)
- Narrow angle flat fan spray pattern
- Sharply defined spray edges
- Pressure range: 15 psi to 150 psi (1 bar to 10 bar)
- Material: brass or stainless steel
- Capacity range: .40 to 20 gpm at 40 psi (1.8 to 91 l/min at 4 bar)



Flat Spray (deflected type)



28500R

Tank Washing Nozzles

Threadless design and stainless steel locking pin provide better seal and prevent contamination


Features and Benefits

- Multiple orifice configuration combined with a rotating motion provides exceptional performance in low-pressure cleaning and rinsing applications
- Meets 3A standards for sanitary environments
- Excellent solution for clean-in-place systems – no external power source is necessary
- Tapered interior surfaces are self-draining
- TEFLON® fluoropolymer resin construction withstands harsh chemical and corrosive environments
- Maximum operating temperature: 200° F (93° C)

Request Bulletin 503B for more information.

*TEFLON® is a registered trademark of E.I. DuPont de Nemours and Company

Conforms to 3A standards for CIP



Ordering Information

28500R Nozzle

| | | | | | | | | | |
|-------------|---------------|---|-----------------------|---|------------------|---|---------------|---|---------------|
| 28500 | E | — | R | — | 3/4 | — | 23 | — | TEF |
| Nozzle Type | Coverage Type | | Removeable Spray Head | | Inlet Connection | | Capacity Size | | Material Code |


Coverage Type

| Spray Angle | 180° Down | 270° Up | 270° Down | 360° |
|----------------------------------|-----------|----------|-----------|----------|
| Type of Coverage (Direct Impact) | B | C | D | E |

Performance Data

| Nozzle No. | in. (mm) | Inlet Conn. in. (Eur) | Capacity gpm (l/min) | | | | |
|---------------------|------------|--------------------------|----------------------|------------------|----------------|----------------|------------------|
| | | | 10 psi (.7 bar) | 20 psi (1.5 bar) | 30 psi (2 bar) | 40 psi 3 (bar) | 50 psi (3.5 bar) |
| 28500 (B thru E)-R- | 3/4 (20) | -18-TEF | 9 (34) | 12.7 (50) | 15.6 (58) | 18 (71) | 20.1 (77) |
| 28500 (B thru E)-R- | 3/4 (20) | -23-TEF | 11.5 (44) | 16.3 (64) | 19.9 (74) | 23 (91) | 26 (99) |
| 28500 (B thru E)-R- | 3/4 (20) | -32-TEF | 16 (61) | 22.6 (89) | 27.7 (103) | 32 (126) | 35.8 (136) |
| 28500 (B thru E)-R- | 3/4 (20) | -46-TEF | 23 (88) | 32.5 (128) | 39.8 (148) | 46 (181) | 51.4 (196) |
| 28500 (B thru E)-R- | 1 (25) | -33-TEF | 16.5 (63) | 23 (92) | 29 (106) | 33 (131) | 37 (141) |
| 28500 (B thru E)-R- | 1 (25) | -50-TEF | 25 (95) | 35.4 (140) | 43.3 (161) | 50 (197) | 55.9 (213) |
| 28500 (B thru E)-R- | 1 (25) | -70-TEF | 35 (133) | 49.5 (195) | 60.6 (226) | 70 (276) | 78.3 (298) |
| 28500 (B thru E)-R- | 1 (25) | -90-TEF | 45 (172) | 63.6 (251) | 77.9 (290) | 90 (355) | 100.6 (384) |
| 28500 (B thru E)-R- | 1-1/2 (40) | -33-TEF | 27 (101) | 37 (148) | 46 (171) | 53 (209) | 59 (226) |
| 28500 (B thru E)-R- | 1-1/2 (40) | -50-TEF | 35 (132) | 49 (185) | 61 (231) | 70 (265) | 78 (295) |

Dimensions



| Nozzle Inlet ID | Inlet Dia. (mm) | X Dia. (mm) | Y (mm) | Z (mm) |
|-----------------|-----------------|---------------|---------------|-------------|
| 3/4" (DN20) | .76" (22.2) | 2-1/4" (57.2) | 2-5/8" (66.6) | 3/8" (9.5) |
| 1" (DN25) | 1.02" (28.2) | 2-3/4" (69.8) | 2-7/8" (73) | 1/2" (12.7) |
| 1-1/2" (DN40) | 1.52" (40.2) | 3-5/8" (92) | 3-5/8" (92) | 3/4" (19) |



Compact Rokon Nozzle

Features and Benefits

- Delivers total impact, constant speed, fluid driven tank wash
- Ideal for high-temperature tank cleaning and sanitation
- Meets 3A standards for sanitary environments
- Rotational speed varies with pressure, 2-30 RPM

Specifications


- Maximum tank size diameter: 12' (3.7 m)
- Capacity range: 2.7 to 34 gpm (10 to 128 l/min)
- Recommended pressure range: 30 to 175 psi (2 to 12 bar)
- Maximum pressure: 290 psi (20 bar)
- Maximum operating temperature: 302° F (150° C)
- Tank opening size: 1-1/4" (32 mm)
- Spray coverage: 360° direct impact
- Material: 316L stainless steel



Conforms to 3A standards for CIP



Coverage Type



Ordering Information

Compact Rokon Rotary Tank Washing Nozzle

D41800E — 19 — 316L — 13.6 — 3A

Nozzle
Type


Material
Code

Capacity
Size

Performance Data

| Nozzle Inlet Connections | Capacity Size | Capacity gmp (l/min) | | | | |
|--------------------------|---------------|----------------------|----------------|-----------------|------------------|------------------|
| | | 20 psi (1.4 bar) | 40 psi (3 bar) | 100 psi (5 bar) | 150 psi (10 bar) | 230 psi (16 bar) |
| 3/4" (DN19) | 3.2 | 2.7 (10) | 3.5 (14) | 5.3 (17) | 6.5 (24) | 7.9 (30) |
| | 4.5 | 3.4 (13) | 4.8 (19) | 7.5 (24) | 9.1 (34) | 11.3 (43) |
| | 9.9 | 7.2 (27.3) | 10.1 (40) | 16.1 (52) | 19.7 (73) | 24 (93) |
| | 13.6 | 9.9 (37.7) | 14 (55) | 22 (71) | 27 (101) | 34 (128) |

Dimensions and Weights



| Inlet Connections | A (mm) | B dia. (mm) | C dia. (mm) | Net Weight lbs (kg) |
|-------------------|---------|--------------|-------------|---------------------|
| 3/4" (DN19) | 3" (78) | 1-3/16" (30) | .13" (3.3) | .26 (0.13) |



Fixed Spray Balls

Features and Benefits

- Ideal for rinsing and low-pressure washing
- Suitable for CIP – no moving parts
- Low maintenance
- Deliver reliable, consistent performance
- Work well with a wide array of CIP chemicals
- Sanitary design with self-cleaning retaining pin inlet connection

Specifications

- Maximum tank size diameter: 18' (5.5 m)
- Capacity: 22 to 141 gpm (83 to 534 l/min)
- Recommended pressure range: 15 to 30 psi (1.03 to 2.06 bar)
- Spray coverage: 180° and 360° direct impact
- Materials: 316L stainless steel






Ordering Information

Fixed Spray Balls

| | | | | | | | | | | | | | | | | | |
|-----------|---|----------------|---|------------------|---|---------------|---|---------------|---|---|---|---|---|---|---|---|---|
| 6 | 3 | 2 | 2 | 5 | B | — | 3 | / | 4 | — | 2 | 2 | — | 3 | 1 | 6 | L |
| Unit Type | | Spray Coverage | | Inlet Connection | | Capacity Size | | Material Code | | | | | | | | | |


Coverage Type

| Spray Angle | 180° Up | 180° Down | 360° |
|----------------------------------|---|---|---|
| Type of Coverage (Direct Impact) |  |  |  |
| | A | B | E |

Performance Data

| Ball Type/Size | Capacity gpm (l/min) | | |
|----------------|----------------------|-------------------|-------------------|
| | 15 psi (1.03 bar) | 22 psi (1.52 bar) | 30 psi (2.06 bar) |
| 63225 – 3/4" | 22 (83) | 27 (102) | 31 (117) |
| 63225 – 1" | 32 (121) | 39 (148) | 45 (170) |
| 63225 – 2" | 100 (379) | 121 (458) | 141 (534) |

Dimensions



| Inlet Connection | Inlet Size A (mm) | Ball Dia. B (mm) | Net Weight lbs (kg) |
|------------------|-------------------|------------------|---------------------|
| 3/4" | .78" (19.81) | 2" (51) | .24 (.11) |
| 1" | 1.03" (26.16) | 2-1/2" (64) | .46 (.21) |
| 2" | 2.03" (51.56) | 3-3/4" (95) | 1.42 (.65) |



Ultra Clean BCFT and QFT Tank Machines

Features and Benefits

- Delivers high impact fluid driven tank washing
- Ideal for cleaning tanks in a hygienic environment
- Four nozzle design for faster cleaning cycles
- Rounded shape eliminates deposit traps ensuring tank sterility
- Suitable for CIP or portable tank cleaning
- Lubricant-free flow through lowers risk of cross contamination
- UCBCFT model is easily modified with short or long nozzles

Specifications


- Capacity: 14 to 168 gpm (53 to 636 l/min)
- Pressure range: 30 to 300 psi (2 to 21 bar)
- Maximum operating temperature: 300° F (149° C)
- Minimum tank opening size:
UCBCFT short nozzle: 4.5" (113 mm)
UCBCFT long nozzle: 4.9" (125 mm)
UCQFT long nozzle: 6.5" (163 mm)
- Spray coverage: 360° direct impact
- Materials: 316 stainless steel with wetted components of food-grade material
- Weight: UCBCFT – 11 lbs. (5 kg)
UCQFT – 15 lbs. (6.81 kg)



UCBCFT Tank Machine

UCQFT Tank Machine

Coverage Type Ordering Information



UltraClean

| UCBCFT—3 | | L |
|-----------|-------------------|------------------------------------|
| Unit Type | Nozzle Size in mm | Long or Short Nozzle (UCBCFT only) |

Performance Data

| Nozzle Type/Size | Capacity gpm (l/min) – Maximum Tank Diameter ft (m) | | | | | | |
|------------------|---|----------------------|----------------------|----------------------|----------------------|--------------------|----------------------|
| | 30 psi (2.1 bar) | 50 psi (3.4 bar) | 100 psi (6.9 bar) | 140 psi (9.7 bar) | 200 psi (13.8 bar) | 250 psi (17.2 bar) | 300 psi (20.7 bar) |
| UCBCFT 3mm | 14 (53) – 32 (10) | 17 (65) – 38 (12) | 20 (75) – 43 (13) | 25 (95) – 50 (15.5) | 28 (107) – 53 (16.5) | 30 (113) – 55 (17) | 32 (122) – 58 (18) |
| UCBCFT 4mm | 22 (83) – 34 (10.5) | 27 (102) – 40 (12.5) | 32 (122) – 46 (14) | 37 (140) – 52 (16) | 40 (152) – 55 (17) | 44 (167) – 59 (18) | 46 (175) – 62 (19) |
| UCBCFT 5mm | 33 (125) – 36 (11) | 40 (152) – 42 (13) | 46 (175) – 47 (14.5) | 55 (208) – 54 (16.5) | 58 (220) – 58 (18) | 63 (238) – 61 (19) | 66 (250) – 64 (19.5) |
| UCBCFT 6mm | 46 (175) – 38 (12) | 55 (208) – 44 (13.5) | 64 (242) – 50 (15.5) | 76 (287) – 56 (17) | 79 (298) – 60 (18.5) | 85 (322) – 65 (20) | 90 (340) – 67 (20.5) |

| Nozzle Type/Size | Capacity gpm (l/min) – Maximum Tank Diameter ft (m) | | | | | | |
|------------------|---|----------------------|----------------------|---------------------|-----------------------|-----------------------|-----------------------|
| | 30 psi (2.1 bar) | 50 psi (3.4 bar) | 100 psi (6.9 bar) | 150 psi (10.3 bar) | 200 psi (13.8 bar) | 250 psi (17.2 bar) | 300 psi (20.7 bar) |
| UCQFT 6mm | 30 (114) – 28 (8.5) | 50 (189) – 36 (11) | 64 (242) – 47 (14.5) | 76 (288) – 56 (17) | 86 (326) – 67 (20.5) | 95 (360) – 74 (23) | 103 (390) – 77 (23.5) |
| UCQFT 7mm | 38 (144) – 30 (9) | 64 (242) – 40 (12.5) | 82 (310) – 52 (16) | 97 (367) – 61 (19) | 110 (416) – 73 (22.5) | 122 (462) – 80 (24.5) | 132 (500) – 83 (25.5) |
| UCQFT 8mm | 48 (182) – 34 (10.5) | 82 (310) – 42 (13) | 106 (401) – 55 (17) | 124 (469) – 65 (20) | 140 (530) – 76 (23.5) | 155 (587) – 82 (25.5) | 168 (636) – 88 (27) |

Rotating Keg and Tank Wash Nozzles

To meet your tank cleaning needs, Spraying Systems Co. manufactures a variety of tank washing nozzles. Whether you require a light rinse or a high-impact wash, you can find the right nozzle for your application.

D26984 Rokon

Designed to increase cleaning impact up to 4x higher than conventional rotating nozzles, the Rokon is excellent for cleaning, sanitizing and foaming applications for both containers and equipment.



23240 Tank Wash Nozzle

Available with one, two or three spray orifices, the 23240 nozzle is great for washing kegs and small barrels.



36640 Keg Washing Nozzle

Ideal for rinsing and light cleaning in small containers, the 36640 nozzle features two rotating flat spray tips that deliver cylindrical spray coverage.



21400A Tank Wash Nozzle

The 21400A nozzle features three high-impact flat sprays that deliver complete orbital coverage for effectively washing barrels and drums. This nozzle is also available in a high temperature model.



D25468 Tank Wash Nozzle

Featuring a self-cleaning sliding bearing, the D25468 nozzle is ideal for rinsing chemical containers and tanks.



18250A Tank Wash Nozzle

The 18250A nozzle features three high-impact flat sprays that deliver complete orbital coverage for effectively washing tanks, barrels and drums. This nozzle is also available in a high temperature model.



Fluid Driven (Constant Speed): 2-30 rpm

| Model Type | Maximum Tank Dia. | Inlet Connection | Spray Angle | Spray Pattern | Max. Liquid Pressure | Maximum Temp. | Materials of Wetted Parts | Maximum Flow |
|--------------|-------------------|------------------|-------------|---------------|----------------------|----------------|---------------------------|----------------------|
| D26984 Rokon | 13-20 ft (4-6 m) | 12", 3/8", 1/2" | 36° | Flat Fan | 290 psi (20 bar) | 160° F (70° C) | 303SS, 316SS, PVDF, PE | 31.2 gpm (128 l/min) |

Fluid Driven (Reactionary Force):

Rotate at high speeds. Driven by reaction force of nozzles.

| Model Type | Maximum Tank Dia. | Inlet Connection | Spray Angle | Spray Pattern | Max. Liquid Pressure | Maximum Temp. | Materials of Wetted Parts | Maximum Flow |
|------------|-------------------|------------------|--------------|---------------|----------------------|----------------|---------------------------|--------------------|
| 23240 | 3 ft (.9 m) | 1/2" | 240° 360° | Flat Fan | 200 psi (14 bar) | 180° F (82° C) | 316SS, HSS, PFTE | 22 gpm (79 l/min) |
| 36640 | 3 ft (.9 m) | 1/4" | 120° | Flat Fan | 100 psi (7 bar) | 200° F (93° C) | 316SS, HSS, PFTE | 2.2 gpm (79 l/min) |
| 21400A | 5 ft (1.5 m) | 3/4" | 360° | Flat Fan | 100 psi (7 bar) | 200° F (93° C) | 316SS, HSS, PFTE | 22 gpm (82 l/min) |
| D25468 | 6.5 ft (2 m) | 1/2" | 240° | Flat Fan | 70 psi (4 bar) | 160° F (70° C) | DELTRIN® 303SS | 9.2 gpm (36 l/min) |
| 18250A | 8 ft (2.4 m) | 3/4" | 360° | Flat Fan | 100 psi (7 bar) | 200° F (93° C) | 316SS, HSS, PFTE | 55 gpm (205 l/min) |

Note: Ratings are approximate. Actual coverage and performance will vary due to pressure and cleaning requirements. DELTRIN® is a registered trademark of E.I. DuPont de Nemours and Company.



Stationary Keg and Tank Wash Nozzles

15498 Keg Wash Nozzle

A low capacity nozzle designed to pass through standard keg bungs and to fit on automatic keg washers. It is perfect for cleaning the interior of small distribution or process kegs.



VSM Wash Nozzle

The VSM nozzle features a durable, corrosion-resistant design and is efficient for rinsing small containers.



3150 Drum Wash Nozzle

A low capacity nozzle designed for optimal cleaning performance in harsh operating conditions. It is excellent for cleaning the interior of small distribution or process drums.



6353 Wash Nozzle

A high capacity nozzle for thorough cleaning of tanks and vessels. It features numerous spray patterns and coverages, and is available in a Maximum Free Passage version.



Fixed Stationary

| Model Type | Maximum Tank Dia. | Inlet Connection | Spray Angle | Spray Pattern | Max. Liquid Pressure | Maximum Temp. | Materials of Wetted Parts | Maximum Flow |
|------------|-------------------|------------------|--------------|---------------|----------------------|------------------|---------------------------|---------------------|
| 15498 | 2 ft (.6 m) | 1" | 270° 360° | Full Cone | 150 psi (10 bar) | 212° F 100° C | Brass, 303SS 316SS | 11.7 gpm (43 l/min) |
| 3150 | 3 ft (.9 m) | 1" | 270° 360° | Full Cone | 150 psi (10 bar) | 212° F 100° C | Brass 303SS | 26 gpm (91 l/min) |
| VSM | 5 ft (1.6 m) | 1/2" 3/4" | 240° | Solid Stream | 140 psi (10 bar) | 200° F 93° C | NYL 303SS | 63 gpm (269 l/min) |
| 6353 | 10 ft (3 m) | 1-1/2" | 360° | Full Cone | 60 psi (4 bar) | 212° F 100° C | Brass, 303SS 316SS | 80 gpm (300 l/min) |

Note: Ratings are approximate. Actual coverage and performance will vary due to pressure and cleaning requirements.


Custom Sanitation Lances

for complete tank wash assemblies

Spraying Systems Co. manufactures tank wash lances in a wide variety of configurations such as quick-release or bolt-on options, adapters, cooling jackets, ceramic linings, purge tubes, protective tubes and more. For specialized applications that are out of the ordinary, we offer custom fabrication to meet your exacting needs.

Custom Options

- Lance Diameter
- Lance Thickness
- Bolt Circle Diameter
- Bolt Diameter
- Lance Length
- Connectors
- Nozzle
- Material: Stainless Steel
Teflon
Polypropylene
Kynar



TEFLON® is a registered trademark of E.I. DuPont de Nemours and Company



WindJet®

Air Knife Drying Packages


A completely customizable package comprised of WindJet Air Knives and a low maintenance regenerative blower system.

Features and Benefits

- A complete package, fully customized for sanitary dry-off applications
- Uniquely designed WindJet Air Knives produce a uniform, high volume, constant air stream
- High-performance air knives eliminate spotting and blotching
- Air knife's leading edge improves setup with added visual reference
- Corrosion-resistant finish and leak-proof end caps on the air knives
- Low-maintenance, direct-drive blower
- Clean, heated air
- Energy-efficient air source
- Low operating noise, requiring no need of a sound closure
- Easy to install and maintain



Figure 1: Conveyor Wash and Blow Off



WindJet Air Knife Drying Package Specifications:*

WindJet Air Knives

Knife Lengths:

6", 12", 18", 24", 30" and 36"

Custom lengths are also available

Air slot sizes:

.040" and .060"

Material:

Aluminum, 316 stainless steel

Gast® Regenerative Blower Assemblies

Available in 5, 10, 15 and 30 HP

Assembly Components:

Pressure relief valve

Pressure gauge

Air inlet filter

Fittings

Convenient mounting adapter for flexible or rigid tubing

Package Accessories

Mounting brackets

Muffler

Flexible and/or rigid tubing

Elbows

Motor starter

Couplings

Clamps

Manifolds

Air cannons

WindJet Nozzles

Very low noise air control nozzles that convert a low-pressure volume of compressed air into a targeted, high-velocity concentrated single or flat fan air stream

Features and Benefits


- Dependable, repeatable performance
- Delivers uniform distribution and spray pattern integrity
- Recessed orifices protect against external damage
- Effectively dries hard-to-reach recesses
- Mounting hole ensures correct positioning on headers and manifolds

AA727

- Flat fan spray with 16 precision orifices
- Mounting hole: 3/16" (4.8 mm) diameter
- 1/4" NPT or BSPT inlet connections
- Capacity range:
5.0 to 43.4 scfm
(142 to 1198 NI/min)
- Pressure range:
10 psi to 90 psi (.7 bar to 6 bar)
- Material: 316 stainless steel



Air Stream



AA707

- Tightly directed round spray pattern
- Interchangeable caps to easily alter capacity
- Caps color-coded for easy identification
- 1/4" NPT or BSPT (M) inlet connections
- Capacity range:
5.2 to 45 scfm
(142 to 1237 NI/min)
- Pressure range:
10 psi to 90 psi
(.7 bar to 6 bar)
- Material: 316 stainless steel



Air Stream



* The number and length of knives, air slot choice, blower size and necessary accessories vary depending on the application. Packages are differentiated by the horsepower size of the included Gast® blower.



Spraying Systems Co.[®]
Experts in Spray Technology

P.O. Box 7900, Wheaton, IL 60189-7900 USA

Tel: 1.800.95.SPRAY Intl. Tel: 1.630.665.5000

Fax: 1.888.95.SPRAY Intl. Fax: 1.630.260.0842

www.spray.com



Spray
Nozzles



Spray
Control



Spray
Analysis



Spray
Fabrication